NAME

rtf2troff − convert Rich Text Format documents to *troff*

SYNTAX

rtf2troff [**−e**] [**−h|+h**] [**−man|−me|−mm|−ms**] [**−s|+s**] [**−t** *troff*] [**−u|+u**] [*file*]

DESCRIPTION

rtf2troff converts documents written in Rich Text Format (RTF) to *troff* format.

Optional flags may be given to modify the operation of *rtf2troff* , as follows:

−e Turn on token echoing. This causes each token read from the input file to be echoed to the output. Not normally useful except for debugging.

−h Turn off header/footer output. This is the default, since most of the time you'll probably run the output through *troff* using a macro package that supplies its own header and footer macros.

+h Turn on header/footer output. *rtf2troff* attempts to write header and footer traps.

−m*xx* Specify macro package, one of **−man**, **−me**, **−mm**, or **−ms**. This usually has little effect, although there are some minor tweaks made to the output that can be macro-package-specific.

−s Disallow strikethrough output. *rtf2troff* simulates strikethrough output by generating *troff* output that prints the struck-through character, backs up, and prints a line through the character. This works reasonably well, but the *troff* output is hideous and difficult to edit.

+s Allow strikethrough output. This is the default.

−t *troff* Specify version of *troff* for which output should be written. The default is *groff* . Other reasonable versions, if you have them, are *dwbtroff* and *pstroff* .

−u Disallow underlined output. *rtf2troff* simulates underlining by generating *troff* output that prints the underlined character, backs up, and prints an underscore. This works reasonably well, but the *troff* output is hideous and difficult to edit.

+u Allow underlined output. This is the default.

SEE ALSO

troff2rtf(1)

WHO-TO-BLAME

Paul DuBois, dubois@primate.wisc.edu