

Math 2250 Maple Project 9, S2014. Tacoma Narrows.

NAME \_\_\_\_\_ CLASSTIME \_\_\_\_\_

There are two (2) problems in this project. Please answer the questions A, B, C , ... associated with each problem. The original worksheet "2250mapleL9-S2014.mws" is a template for the solution; you must fill in the code and all comments. Sample code can be copied with the mouse. Use pencil freely to annotate the worksheet and to clarify the code and figures.

The problem headers for the S2014 revision of David Eyre's project (original was year 2000).

-----L9.1. NONLINEAR MCKENNA MODELS  
-----L9.2. MCKENNA NON-HOOKES LAW CABLE MODEL.

#### L9-1. PROBLEM (NONLINEAR MCKENNA MODELS)

There are three (3) parts L9-1A, L9-1B, L9-1C to complete. Mostly, this is mouse copying. Retyping the maple code by hand is not recommended.

NONLINEAR TORSIONAL MODEL WITH GEOMETRY INCLUDED.

Consider the nonlinear, forced, damped oscillator equation for torsional motion, with bridge geometry included,

$$x'' + 0.05 x' + 2.4 \sin(x)\cos(x) = 0.06 \cos(12 t/10) ,$$
$$x(0) = x_0, \quad x'(0) = v_0$$

and its corresponding linearized equation

$$x'' + 0.05 x' + 2.4 x = 0.06 \cos(12 t/10) ,$$
$$x(0) = x_0, \quad x'(0) = v_0.$$

The spring-mass system parameters are  $m=1$ ,  $c = 0.05$ ,  $k = 2.4$ ,  $w = 1.2$  ,  $F = 0.06$ . Maple code used to solve and plot the solutions appears below.

```
# Mouse copy into a maple worksheet.
x0:=0: a:=200: b:=300: # For part A. Change it for part B!
v0:=0: m:=1: F := 0.06: w := 1.2: m:=1: c:= 0.05: k:= 2.4:
with(DEtools): opts:=stepsize=0.1:
deLinear:= m*diff(x(t),t,t) + c*diff(x(t),t) + k*x(t) = F*cos(w*t):
ICLinear:=[[x(0)=x0,D(x)(0)=v0]]:
DEplot(deLinear,x(t),t=a..b,ICLinear,opts,title='Linear');
deNonLinear:= m*diff(x(t),t,t) + c*diff(x(t),t) +
k*sin(x(t))*cos(x(t)) = F*cos(w*t):
ICNonlinear:=[[x(0)=x0,D(x)(0)=v0]]:
DEplot(deNonLinear,x(t),t=a..b,ICNonlinear,opts,title='NonLinear');
```

9-1A. Let  $x_0=0$ ,  $v_0=0$ . Plot the solutions of the linear and nonlinear equations from  $t=200$  to  $t=300$ . These plots represent the steady state solutions of the two equations.

9-1B. Let  $x_0=1.2$ ,  $v_0=0$ . Plot the solutions of the linear and

nonlinear equations from  $t=220$  to  $t=320$ . These plots represent the steady state solutions of the two equation, with new starting value  $x_0=1.2$ . [You must modify line 1 of the maple code!]

The two linear plots in A and B have to be identical to the plot of  $x_{ss}(t)$ . The reason is the superposition formula (see E&P)  $x(t)=x_h(t)+x_{ss}(t)$ , even though the homogeneous solution  $x_h(t)$  is different for the two plots. This is because  $x_h(t)$  has limit zero at  $t=\infty$ .

- 9-1C. Determine the ratio of the apparent amplitudes (a number  $> 1$ ) for the nonlinear plots in A and B. Do "large sustained oscillations" appear in the plot of the nonlinear steady-state?

#### L9-2. PROBLEM ( MCKENNA'S NON-HOOKE'S LAW CABLE MODEL)

There are three (3) parts L9-2A, L9-2B, L9.2C to complete. Mostly, this is mouse copying. Retyping the maple code by hand is not recommended.

The model of McKenna studies the bridge with a nonlinear, forced, damped oscillator equation for torsional motion that accounts for the non-Hooke's law cables coupled to the equations for vertical motion. The equations in this case couple the torsional motion with the vertical motion. The equations are:

$$\begin{aligned} x'' + c x' - k G(x,y) &= F \sin wt, & x(0) &= x_0, & x'(0) &= x_1, \\ y'' + c y' + (k/3) H(x,y) &= g, & y(0) &= y_0, & y'(0) &= y_1, \end{aligned}$$

where  $x(t)$  is the torsional motion and  $y(t)$  is the vertical motion. The functions  $G(x,y)$  and  $H(x,y)$  are the models of the force generated by the cable when it is contracted and stretched. Below is sample code for writing the differential equations and for plotting the solutions. It is ready for mouse copy.

```
with(DEtools):
w := 1.3: F := 0.05: f(t) := F*sin(w*t):
c := 0.01: k1 := 0.2: k2 := 0.4: g := 9.8: L := 6:
STEP:=x->piecewise(x<0,0,1):
fp(t) := y(t)+(L*sin(x(t))):
fm(t) := y(t)-(L*sin(x(t))):
Sm(t) := STEP(fm(t))*fm(t):
Sp(t) := STEP(fp(t))*fp(t):
sys := {
  diff(x(t),t,t) + c*diff(x(t),t) - k1*cos(x(t))*(Sm(t)-Sp(t))=f(t),
  diff(y(t),t,t) + c*diff(y(t),t) + k2*(Sm(t)+Sp(t)) = g}:
ic := [[x(0)=0, D(x)(0)=0, y(0)=27.25, D(y)(0)=0]]:
vars:=[x(t),y(t)]:
opts:=stepsize=0.1:
DEplot(sys,vars,t=0..300,ic,opts,scene=[t,x]);
```

The amazing thing that happens in this simulation is that the large vertical oscillations take all the tension out of the springs and they induce large torsional oscillations.

L9-2A. TORSIONAL OSCILLATION PLOT. Get the sample code above to produce the plot of  $x(t)$  [that's what `scene=[t,x]` means].

L9-2B. ROADWAY TILT ANGLE. Estimate the number of degrees the roadway tilts based on the plot. Recall that  $x$  in the plot is reported in radians. Comment on the agreement of this result with historical data and the video evidence in the film clip.

Tip: Average the five largest amplitudes in the plot to find an average maximum amplitude for  $t=0$  to  $t=300$ . Convert to degrees using  $\text{Pi radians} = 180 \text{ degrees}$ . The film clip shows roadway maximum tilt of 30 to 45 degrees, approximately.

L9-2C. VERTICAL OSCILLATION PLOT. Modify the `DEplot` code to `scene=[t,y]` and plot the oscillation  $y(t)$  on  $t=0$  to  $t=300$ . The plot is supposed to show 30-foot vertical oscillations along the roadway that dampen to 7-foot vertical oscillations after 300 seconds.

The agreement between these oscillation results and the historical data for Tacoma Narrows, especially the visual data present in the film clip of the bridge disaster, should be clear from the plots. This is your only answer check for the plot results.